


Snow Dragon Industrial Co . , Ltd


Package Dimensions



Notes

1. All dimensions are in millimeters (mm).
2. Tolerance is $\pm 0.25\text{mm}$ unless otherwise noted.
3. Lead spacing is measured where the leads emerge from the package.
4. Specifications are subject to change without notice.

Spatial Distribution



PART NUMBER	REV	PAGE	DATE
20W白灯	R101	1/2	2009-03-04

Snow Dragon Industrial Co . , Ltd

Electrical / Optical Characteristics at TA=25°C

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Luminous Intensity	Φ	1000	1100	1200	lm	IF = 1400mA
Viewing Angle	$2\theta_{1/2}$	110	115	120	deg	IF = 1400mA
Dominant Wavelength	Tc	6000	6500	7000	K	IF = 1400mA
Spectral Line Half-Width	$\Delta\lambda$				nm	IF = 1400mA
Forward Voltage	VF	15	16	18	V	IF = 1400mA
Reverse Current	IR			20	μA	VR = 5V

Absolute Maximum Ratings at TA=25°C

Parameter	Maximum Rating
Power Dissipation	20W
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	3000mA
Continuous Forward Current	1400mA
Reverse Voltage	5V
Operating Temperature Range	-20°C to + 60°C
Storage Temperature Range	-20°C to + 60°C
Lead Soldering Temperature [1.6mm(.063") From Body]	260°C for 5 Seconds

PART NUMBER	REV	PAGE	DATE
20W白灯	R101	2/2	2009-03-04