

Snowdragon Industrial Co.,Ltd

DATA SHEET

MODEL No : SD-2352 AX

ENG. No:

PREPARED BY	CHECKED BY	APPROVED BY
CUSTOMER APPROVED SIGNATURES		

	ATTENTION OBSERVE PRECAUTIONS ELECTROSTATIC SENSITIVE DEVICES
---	---



FEATURES

- *0.25inch (6.2 mm) DIGIT HEIGHT
- *CONTINUOUS UNIFORM SEGMENTS
- *LOW POWER REQUIREMENT
- *EXCELLENT CHARACTERS APPEARANCE
- *WIDE VIEWING ANGLE
- *SOLID STATE RELIABILITY


DESCRIPTION

- *The 0.25 inch (6.2mm) digit height 4 digit seven-segment icon display.
- *The device is single-color (green) applicable display.
- *The device has a black face and white segments.


DEVICE

PART NO.	DESCRIPTION
GREEN	Multiplex Common Cathode
SD-2352 AX	

PACKAGE DIMENSIONS



INTERNAL CIRCUIT DIAGRAM



NOTES: All dimensions are in millimeters. Tolerances are ± 0.25 mm unless otherwise noted.

ABSOLUTE MAXIMUM RATING

PARAMETER	SYMBOL		green		UNIT
PowerDissipationPerChip	Pd		87		mW
Peak Forward Current Per Chip (Frequency 1Khz,10%duty cycle)	Ifp		100		mA
Continuous Forward Current Per Chip Derating Linear From 25°C Per Chip	IF		25		mA
			0.33		mA/°C
Reverse Voltage Per Chip	VR		5		V
Operating Temperature Range	TA	-25°C to +85°C			
Storage Temperature Range	Tstg	-25°C to +85°C			

Solder Temperature:max 260°C for max 3 sec at 1.6mm below seating plane

*see figure 5 to establish pulsed condition


ELECTRICAL/OPTICAL CHARACTERISTICS AT Ta=25°C

PARAMETER		SYMBOL	MIN	TYP	MAX	UNIT	TEST CONDITION
Average luminous intensity per segment		IV	/	/	/	mcd	If=10mA
	green		290	/	310		
			/	/	/		
Dominant wavelength		λ d	/	/	/	nm	If=20mA
	green		520	/	525		
			/	/	/		
Spectral line half-width	green	Δ λ	20			Nm	If=20mA
Forward voltage per chip		Vf	/	/	/	V	If=20mA
	green		/	3.0	3.5		
			/	/	/		
Reverse current per chip		Ir	10			uA	VR=5v
Luminous intensity matching ratio		iv-m	2:1				If=10mA


Note:Luminous intensity is measured with a light sensor and filter combination that approximates the CIE (Commision Internationale De L'Eclairage) eye-response curve.

TYPICAL ELECTRICAL / OPTICAL CHARACTERISTIC CURVES
(25 °C Ambient Temperature Unless Otherwise Noted)


TYPICAL ELECTRICAL–OPTICAL CHARACTERISTICS CURVES




- RELATIVE INTENSITY Vs wavelength(λ_p)
- (1)–GaAsP GaAs655nm/Red
 - (6)–GaAlAs/GaAs 660nm/Super Red
 - (A)–GaN/sic430nm/Blue
 - (2)–GaP 568nm/Yellow Green
 - (7)–GaAsP/Ga610nm/Super Red
 - (B)–InGaN/sic470nm/Blue
 - (3)–GaAsP/GaP 585nm/Yellow
 - (8)–GaAlAs880nm
 - (C)–InGaN/sic502nm/Ultra Green
 - (4)–GaAsP/GaP 635nm/Orange ?Hi–Eff Red
 - (9)–GaAs/GaAs&GaAlAs/GaAs940nm
 - (D)–InGaAl/sic523nm/Ultra Green
 - (5)–GaP 700nm/Bright Red




RELATIVE LUMINOUS INTENSITY VS.FORWARD CURRENT




FORWARD CURRENT VS.AMBIENT TEMPERATURE




AMBIENT TEMPERATURE Ta(°C)



FORWARD VOLTAGE (Vf) FORWARD CURRENT VS.FORWARD VOLTAGE



NOTE: 25°C free air temperature unless otherwise specified.



TYPICAL ELECTRICAL-OPTICAL CHARACTERISTICS CURVES

LED NUMERIC RELIABILITY

• Test Items And Results

Type	Test Item	REF. Standard	Test Condition	Note	Number of Damaged
Environmental Sequence	Temperature Cycle	JIS C 7021 (1997) A-4	-20°C → 25°C → 80°C → 25°C 30mins,5mins,30mins,5mins	100 cycles	0/100
	High Humidity Heat Cycle	JIS C 7021 (1997) A-5	30°C → 65°C 90%RH 24hrs/1cycle	10 cycles	0/100
	High Temperature Storage	JIS C 7021 (1997) B-10	Ta=80°C	1000hrs	0/100
	Humidity Heat Storage	JIS C 7021 (1997) B-11	Ta=60°C RH=90%	1000hrs	0/100
	Low Temperature Storage	JIS C 7021 (1997) B-12	Ta= -30°C	1000hrs	0/100
Operation Sequence	Life Test	JIS C 7035 (1985)	Ta=25°C I _F =20mA	1000hrs	0/100
	High Humidity Heat Life Test	*	60°C RH=90% I _F =20mA	500hrs	0/100
	Low Temperature Life Test	*	Ta= -20 °C I _F =20mA	1000hrs	0/100
Destructive Sequence	Resistance to Soldering Heat	JIS C 7021 (1997) A-11	Tsol=260 ± 5°C,10sec (3mm from the base of the epoxy bulb)	1 time	0/20
	Solderability	JIS C 7021 (1997) A-2	Tsol=235 ± 5°C,5sec (Using flux)	1 time (over 95%)	0/20
	Lead Pull/Bend Test	JIS C 7021 (1997)A-11	Load 2.5N (0.25kgf) 0° → 90° → 0° Bending 3 times	No noticeable damage	0/20

* Refer to reliability test standard specification for in this line.

• Criteria for Judging The Damage

Item	Symbol	Test Condition	Criteria for Judgment	
			Min.	Max.
Forward Voltage	V _F	I _F = 20mA	---	Initial data x 1.1
Reverse Current	I _R	V _R = 5V	---	Initial data x 2.0
Luminous Intensity	I _v	I _F = 20mA	Initial data x 0.7	---